



WORLD OF TAPE LTD.

#4451 / 3 DOUBLE COATED POLYESTER

Description	Thin Polyester carrier coated with high grade rubber based hot melt pressure sensitive adhesive.
Features	High adhesion level. Strong carrier. Excellent aging Characteristics.
Application	Splicing and laminating of general and difficult Substrates.

Typical Properties

Thickness:(Adhesive on each side)	Micron	39 (1.5)	Test method
Carrier:	(mil)	12 (0.4)	<i>PSTC-33</i>
Liner:		70 (2.7)	
Total:		160 (6.1)	
Tensile Str:	N/mm ²	260	<i>PSTC-31</i>
Elongation:	%	130	<i>PSTC-31</i>
Peel Adhesion 180° From Stainless Steel:	N/in Oz/in	34 120	<i>PSTC-3</i> (28 mic Polypro Support)
Tape Colour:	Transparent		
Temperature Range:	- 10° C / +70° C		
Liner Colour:	White		

Storage and shelf life: One year when stored at 21°C / 50% relative humidity out of direct sunlight.

Note: Before using, user shall determine the suitability of the product for their intended use. Every Possible effort has been made to furnish tapes suitable for the purposes intended. However, uses of the tapes are beyond our control and our products are necessarily sold Without warranties, expressed or implied.

VANCOUVER

11191 Horseshoe Way, Unit # 9
Richmond, B. C. V7A 4S5
Tel: (604) 272-4550
Fax: (604) 272-4552

TORONTO

42 Goodmark Pl., Unit 7 - 14
Rexdale, Ontario M9W 5S8
Tel: (416) 674-6833
Fax: (416) 674-6763

MONTREAL

393 Rue Dozois
Granby, Quebec J2H 1H6
Tel: (514) 372-8474
Fax: (514) 372-9673

Toll Free: 1-888-995-9189

www.worldoftape.com